

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product Description: **tert-Butyldimethylchlorosilane, 50% w/w in toluene**  
Cat No. : **B21286**

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.  
Uses advised against No Information available

### 1.3. Details of the supplier of the safety data sheet

Company Avocado Research Chemicals Ltd.  
(Part of Thermo Fisher Scientific)  
Shore Road, Heysham  
Lancashire, LA3 2XY,  
United Kingdom  
Office Tel: +44 (0) 1524 850506  
Office Fax: +44 (0) 1524 850608

E-mail address begel.sdsdesk@thermofisher.com

### 1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11  
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99  
**CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

### Poison Centre - Emergency information services

**Ireland** : National Poisons Information Centre (NPIC) -  
**01 809 2166** (8am-10pm, 7 days a week)  
**Malta** : +356 2395 2000  
**Cyprus** : +357 2240 5611

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

#### GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

##### Physical hazards

Flammable liquids Category 2 (H225)

##### Health hazards

Aspiration Toxicity Category 1 (H304)

# SAFETY DATA SHEET

tert-Butyldimethylchlorosilane, 50% w/w in toluene

Revision Date 30-Nov-2024

Skin Corrosion/Irritation	Category 1 A (H314)
Serious Eye Damage/Eye Irritation	Category 1 (H318)
Reproductive Toxicity	Category 2 (H361d)
Specific target organ toxicity - (single exposure)	Category 3 (H336)
Specific target organ toxicity - (repeated exposure)	Category 2 (H373)
<b>Environmental hazards</b>	
Chronic aquatic toxicity	Category 2 (H411)

Full text of Hazard Statements: see section 16

## 2.2. Label elements



Signal Word

Danger

### Hazard Statements

- H225 - Highly flammable liquid and vapor
- H304 - May be fatal if swallowed and enters airways
- H314 - Causes severe skin burns and eye damage
- H336 - May cause drowsiness or dizziness
- H361d - Suspected of damaging the unborn child
- H373 - May cause damage to organs through prolonged or repeated exposure
- H411 - Toxic to aquatic life with long lasting effects

### Precautionary Statements

- P280 - Wear protective gloves/protective clothing/eye protection/face protection
- P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
- P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
- P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- P310 - Immediately call a POISON CENTER or doctor/physician
- P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

## 2.3. Other hazards

- Toxic to terrestrial vertebrates
- This product does not contain any known or suspected endocrine disruptors

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

Component	CAS No	EC No	Weight %	GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
-----------	--------	-------	----------	---

# SAFETY DATA SHEET

tert-Butyldimethylchlorosilane, 50% w/w in toluene

Revision Date 30-Nov-2024

Toluene	108-88-3	203-625-9	50	Flam. Liq. 2 (H225) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 (H336) Repr. 2 (H361d) STOT RE 2 (H373)
Silane, chloro(1,1-dimethylethyl)dimethyl-	18162-48-6	EEC No. 242-042-4	50	Flam. Sol. 2 (H228) Skin Corr. 1A (H314) Eye Dam. 1 (H318) Aquatic Chronic 2 (H411)

Components	Reach Registration Number	
Toluene	01-2119471310-51	
Silane, chloro(1,1-dimethylethyl)dimethyl-	01-2120806537-53	

Full text of Hazard Statements: see section 16

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

<b>General Advice</b>	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
<b>Skin Contact</b>	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately.
<b>Ingestion</b>	Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
<b>Inhalation</b>	If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately. Risk of serious damage to the lungs (by aspiration).
<b>Self-Protection of the First Aider</b>	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

### 4.2. Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes to Physician</b>	Treat symptomatically. Symptoms may be delayed.
---------------------------	---

## SECTION 5: FIREFIGHTING MEASURES

# SAFETY DATA SHEET

tert-Butyldimethylchlorosilane, 50% w/w in toluene

Revision Date 30-Nov-2024

## 5.1. Extinguishing media

### **Suitable Extinguishing Media**

Water mist may be used to cool closed containers. CO<sub>2</sub>, dry chemical, dry sand, alcohol-resistant foam.

### **Extinguishing media which must not be used for safety reasons**

Water.

## 5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Reacts violently with water.

### **Hazardous Combustion Products**

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), Silicon dioxide, Hydrogen chloride gas.

## 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### 6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

### 6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

### 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Do not expose spill to water.

### 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

## **SECTION 7: HANDLING AND STORAGE**

### 7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water. Handle under an inert atmosphere.

### **Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

### 7.2. Conditions for safe storage, including any incompatibilities

Flammables area. Corrosives area. Keep away from heat, sparks and flame. Keep away from water or moist air. Store under an

# SAFETY DATA SHEET

tert-Butyldimethylchlorosilane, 50% w/w in toluene

Revision Date 30-Nov-2024

inert atmosphere. Keep containers tightly closed in a dry, cool and well-ventilated place.

Technical Rules for Hazardous Substances (TRGS) 510  
Storage Class (LGK) (Germany)

Class 3

## 7.3. Specific end use(s)

Use in laboratories

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Toluene	STEL: 100 ppm 15 min STEL: 384 mg/m <sup>3</sup> 15 min TWA: 50 ppm 8 hr TWA: 191 mg/m <sup>3</sup> 8 hr Skin	TWA: 50 ppm (8hr) TWA: 192 mg/m <sup>3</sup> (8hr) STEL: 100 ppm (15min) STEL: 384 mg/m <sup>3</sup> (15min) Skin	TWA: 192 mg/m <sup>3</sup> 8 hr. TWA: 50 ppm 8 hr. STEL: 384 mg/m <sup>3</sup> 15 min STEL: 100 ppm 15 min Skin

#### Biological limit values

List source(s):

#### Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Toluene 108-88-3 ( 50 )				DNEL = 384mg/kg bw/day
Silane, chloro(1,1-dimethylethyl)dimeth yl- 18162-48-6 ( 50 )				DNEL = 1.2mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Toluene 108-88-3 ( 50 )	DNEL = 384mg/m <sup>3</sup>	DNEL = 384mg/m <sup>3</sup>	DNEL = 192mg/m <sup>3</sup>	DNEL = 192mg/m <sup>3</sup>
Silane, chloro(1,1-dimethylethyl)dimeth yl- 18162-48-6 ( 50 )			DNEL = 9.3mg/m <sup>3</sup>	DNEL = 4.1mg/m <sup>3</sup>

#### Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water	Water Intermittent	Microorganisms in	Soil (Agriculture)
-----------	-------------	-------------	--------------------	-------------------	--------------------

# SAFETY DATA SHEET

tert-Butyldimethylchlorosilane, 50% w/w in toluene

Revision Date 30-Nov-2024

		sediment		sewage treatment	
Toluene 108-88-3 ( 50 )	PNEC = 0.68mg/L	PNEC = 16.39mg/kg sediment dw	PNEC = 0.68mg/L	PNEC = 13.61mg/L	PNEC = 2.89mg/kg soil dw
Silane, chloro(1,1-dimethylethyl)di methyl- 18162-48-6 ( 50 )	PNEC = 0.2mg/L	PNEC = 0.54mg/kg sediment dw		PNEC = 66.7mg/L	PNEC = 0.34mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
Toluene 108-88-3 ( 50 )	PNEC = 0.68mg/L	PNEC = 16.39mg/kg sediment dw			
Silane, chloro(1,1-dimethylethyl)di methyl- 18162-48-6 ( 50 )	PNEC = 0.02mg/L	PNEC = 0.054mg/kg sediment dw		PNEC = 16.7mg/kg food	

## 8.2. Exposure controls

### Engineering Measures

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

### Personal protective equipment

#### Eye Protection

Goggles (European standard - EN 166)

#### Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber	See manufacturers	-	EN 374	(minimum requirement)
Viton (R)	recommendations			

#### Skin and body protection

Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

#### Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

#### Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

**Recommended Filter type:** Organic gases and vapours filter Type A Brown conforming to EN14387

#### Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

**Recommended half mask:-** Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141

# SAFETY DATA SHEET

tert-Butyldimethylchlorosilane, 50% w/w in toluene

Revision Date 30-Nov-2024

When RPE is used a face piece Fit Test should be conducted

**Environmental exposure controls** Prevent product from entering drains. Do not allow material to contaminate ground water system.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance		
Odor	No information available	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	110 - 126 °C / 230 - 258.8 °F	
Flammability (liquid)	Highly flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	4 °C / 39.2 °F	<b>Method -</b> No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	No data available	
Water Solubility	Reacts with water	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	<b>log Pow</b>	
Toluene	2.73	
Vapor Pressure	No data available	
Density / Specific Gravity	0.866	
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

### 9.2. Other information

**Explosive Properties** Vapors may form explosive mixtures with air

## SECTION 10: STABILITY AND REACTIVITY

**10.1. Reactivity** None known, based on information available

**10.2. Chemical stability** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous Polymerization** Hazardous polymerization does not occur.  
**Hazardous Reactions** None under normal processing.

**10.4. Conditions to avoid** Incompatible products. Heat, flames and sparks. Exposure to moist air or water. Keep away from open flames, hot surfaces and sources of ignition.

# SAFETY DATA SHEET

tert-Butyldimethylchlorosilane, 50% w/w in toluene

Revision Date 30-Nov-2024

## 10.5. Incompatible materials

Strong oxidizing agents. Water. Strong acids. Strong bases. Amines. Aldehydes. Ketones.

## 10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Silicon dioxide. Hydrogen chloride gas.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Product Information

##### (a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

#### Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Toluene	> 5000 mg/kg ( Rat )	LD50 = 12000 mg/kg ( Rabbit )	26700 ppm ( Rat ) 1 h
Silane, chloro(1,1-dimethylethyl)dimethyl-	>2000 mg/kg (Rat)	-	-

##### (b) skin corrosion/irritation;

Category 1 A

##### (c) serious eye damage/irritation;

Category 1

##### (d) respiratory or skin sensitization;

Respiratory

No data available

Skin

No data available

##### (e) germ cell mutagenicity;

No data available

##### (f) carcinogenicity;

No data available

There are no known carcinogenic chemicals in this product

##### (g) reproductive toxicity;

Reproductive Effects  
Developmental Effects  
Teratogenicity

Category 2

Experiments have shown reproductive toxicity effects on laboratory animals.

Possible risk of harm to the unborn child.

Teratogenic effects have occurred in experimental animals.

##### (h) STOT-single exposure;

Category 3

Results / Target organs

Central nervous system (CNS).

##### (i) STOT-repeated exposure;

Category 2

Target Organs

Skin, Respiratory system, Eyes, Gastrointestinal tract (GI), Liver, Kidney, Neuropsychological effects, Ears.

##### (j) aspiration hazard;

Category 1



# SAFETY DATA SHEET

tert-Butyldimethylchlorosilane, 50% w/w in toluene

Revision Date 30-Nov-2024

**Symptoms / effects, both acute and delayed** Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

## 11.2. Information on other hazards

**Endocrine Disrupting Properties** Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

**Ecotoxicity effects** The product contains following substances which are hazardous for the environment. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Toluene	50-70 mg/L LC50 96 h 5-7 mg/L LC50 96 h 15-19 mg/L LC50 96 h 28 mg/L LC50 96 h 12 mg/L LC50 96 h	EC50: = 11.5 mg/L, 48h (Daphnia magna) EC50: 5.46 - 9.83 mg/L, 48h Static (Daphnia magna)	EC50: = 12.5 mg/L, 72h static (Pseudokirchneriella subcapitata) EC50: > 433 mg/L, 96h (Pseudokirchneriella subcapitata)

Component	Microtox	M-Factor
Toluene	EC50 = 19.7 mg/L 30 min	

**12.2. Persistence and degradability** No information available

#### Persistence

Persistence is unlikely, based on information available.

Component	Degradability
Toluene 108-88-3 ( 50 )	86% (20d)

#### Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants. Water reactive.

### 12.3. Bioaccumulative potential

Product does not bioaccumulate due to reaction with water

Component	log Pow	Bioconcentration factor (BCF)
Toluene	2.73	90

### 12.4. Mobility in soil

No information available Is not likely mobile in the environment.

### 12.5. Results of PBT and vPvB assessment

No data available for assessment.

### 12.6. Endocrine disrupting properties

#### Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

### 12.7. Other adverse effects

#### Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance  
This product does not contain any known or suspected substance

# SAFETY DATA SHEET

tert-Butyldimethylchlorosilane, 50% w/w in toluene

Revision Date 30-Nov-2024

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

<b>Waste from Residues/Unused Products</b>	Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.
<b>Contaminated Packaging</b>	Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.
<b>European Waste Catalogue (EWC)</b>	According to the European Waste Catalog, Waste Codes are not product specific, but application specific.
<b>Other Information</b>	Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms. Do not let this chemical enter the environment.

## SECTION 14: TRANSPORT INFORMATION

### IMDG/IMO

<b>14.1. UN number</b>	UN2920
<b>14.2. UN proper shipping name</b>	CORROSIVE LIQUID, FLAMMABLE, N.O.S.
<b>Technical Shipping Name</b>	tert-Butyldimethylsilyl chloride, toluene
<b>14.3. Transport hazard class(es)</b>	8
<b>Subsidiary Hazard Class</b>	3
<b>14.4. Packing group</b>	I

### ADR

<b>14.1. UN number</b>	UN2920
<b>14.2. UN proper shipping name</b>	CORROSIVE LIQUID, FLAMMABLE, N.O.S.
<b>Technical Shipping Name</b>	tert-Butyldimethylsilyl chloride, toluene
<b>14.3. Transport hazard class(es)</b>	8
<b>Subsidiary Hazard Class</b>	3
<b>14.4. Packing group</b>	I

### IATA

<b>14.1. UN number</b>	UN2920
<b>14.2. UN proper shipping name</b>	CORROSIVE LIQUID, FLAMMABLE, N.O.S.
<b>Technical Shipping Name</b>	tert-Butyldimethylsilyl chloride, toluene
<b>14.3. Transport hazard class(es)</b>	8
<b>Subsidiary Hazard Class</b>	3
<b>14.4. Packing group</b>	I

<b>14.5. Environmental hazards</b>	Dangerous for the environment Product is a marine pollutant according to the criteria set by IMDG/IMO
------------------------------------	--

<b>14.6. Special precautions for user</b>	No special precautions required.
---	----------------------------------

<b>14.7. Maritime transport in bulk according to IMO instruments</b>	Not applicable, packaged goods
--	--------------------------------

# SAFETY DATA SHEET

tert-Butyldimethylchlorosilane, 50% w/w in toluene

Revision Date 30-Nov-2024

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Toluene	108-88-3	203-625-9	-	-	X	X	KE-33936	X	X
Silane, chloro(1,1-dimethylethyl)dimethyl-	18162-48-6	242-042-4	-	-	X	X	97-3-163	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Toluene	108-88-3	X	ACTIVE	X	-	X	X	X
Silane, chloro(1,1-dimethylethyl)dimethyl-	18162-48-6	X	ACTIVE	-	X	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

#### Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Toluene	108-88-3	-	Use restricted. See entry 48. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details)	-
Silane, chloro(1,1-dimethylethyl)dimethyl-	18162-48-6	-	-	-

#### REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

#### Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Toluene	108-88-3	Not applicable	Not applicable
Silane, chloro(1,1-dimethylethyl)dimethyl-	18162-48-6	Not applicable	Not applicable

#### Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

#### Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

# SAFETY DATA SHEET

tert-Butyldimethylchlorosilane, 50% w/w in toluene

Revision Date 30-Nov-2024

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

Take note of Directive 94/33/EC on the protection of young people at work

Take note of Dir 92/85/EC on the protection of pregnant and breastfeeding women at work

## National Regulations

**UK** - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

## WGK Classification

Water endangering class = 2 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Toluene	WGK3	
Silane, chloro(1,1-dimethylethyl)dimethyl	WGK2	

Component	France - INRS (Tables of occupational diseases)
Toluene	Tableaux des maladies professionnelles (TMP) - RG 4bis,RG 84

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Toluene 108-88-3 ( 50 )	Prohibited and Restricted Substances	Group I	

## 15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

## SECTION 16: OTHER INFORMATION

### Full text of H-Statements referred to under sections 2 and 3

H304 - May be fatal if swallowed and enters airways

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H336 - May cause drowsiness or dizziness

H361d - Suspected of damaging the unborn child

H373 - May cause damage to organs through prolonged or repeated exposure

H411 - Toxic to aquatic life with long lasting effects

H225 - Highly flammable liquid and vapor

H228 - Flammable solid

H315 - Causes skin irritation

### Legend

**CAS** - Chemical Abstracts Service

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

# SAFETY DATA SHEET

tert-Butyldimethylchlorosilane, 50% w/w in toluene

Revision Date 30-Nov-2024

KECL - Korean Existing and Evaluated Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

**Key literature references and sources for data**

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadviser - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

**Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:**

**Physical hazards** On basis of test data

**Health Hazards** Calculation method

**Environmental hazards** Calculation method

## Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Chemical incident response training.

**Prepared By** Health, Safety and Environmental Department

**Creation Date** 29-Jun-2010

**Revision Date** 30-Nov-2024

**Revision Summary** Not applicable.

**This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.**

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**