

according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended

Creation Date 17-May-2018 Revision Date 20-Feb-2024 Revision Number 3

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Sponge Nickel, A-4000, promoted with 2% Iron and 2.5% Chromium

Cat No.: 44866

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals. Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

Avocado Research Chemicals Ltd. (Part of Thermo Fisher Scientific)

Shore Road, Heysham Lancashire, LA3 2XY, United Kingdom

Office Tel: +44 (0) 1524 850506 Office Fax: +44 (0) 1524 850608

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Physical hazards

Self-heating substances/mixtures

Category 1 (H251)

Pyrophoric solids

Category 1 (H250)

Health hazards

Skin Sensitization Category 1 (H317)
Carcinogenicity Category 2 (H351)
Specific target organ toxicity - (repeated exposure) Category 1 (H372)

ALFAA44866

Sponge Nickel, A-4000, promoted with 2% Iron and 2.5% Chromium

Revision Date 20-Feb-2024

Environmental hazards

Full text of Hazard Statements: see section 16

2.2. Label elements

Contains Nickel/Aluminium alloy



Signal Word

Danger

Hazard Statements

H251 - Self-heating: may catch fire

H250 - Catches fire spontaneously if exposed to air

H317 - May cause an allergic skin reaction

H351 - Suspected of causing cancer

H372 - Causes damage to organs through prolonged or repeated exposure if inhaled

Precautionary Statements

P201 - Obtain special instructions before use

P235 + P410 - Keep cool. Protect from sunlight

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P231 + P232 - Handle and store contents under inert gas. Protect from moisture

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P302 + P335 + P334 - IF ON SKIN: Brush off loose particles from skin. Immerse in cool water or wrap in wet bandages

2.3. Other hazards

Do not allow evaporation to dryness; Hydrogen gas

Toxicity to Soil Dwelling Organisms

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Component	CAS No	EC No	Weight %	CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Nickel	7440-02-0	EEC No. 231-111-4	86	Flam. Sol. 2 (H228) Skin Sens. 1 (H317) Carc. 2 (H351) STOT RE 1 (H372)
Aluminium	7429-90-5	EEC No. 231-072-3	8.5	Pyr. Sol. 1 (H250) Water-react. 2 (H261)
Chromium	7440-47-3	EEC No. 231-157-5	2.5	-
Iron	7439-89-6	EEC No. 231-096-4	2	-

Sponge Nickel, A-4000, promoted with 2% Iron and 2.5% Chromium

Molybdenum 7439-98-7 EEC No. 231-107-2 1 -

Note

Water

Slurry

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice If symptoms persist, call a physician.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

Ingestion Clean mouth with water and drink afterwards plenty of water. Get medical attention if

symptoms occur.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

May cause allergic skin reaction. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest

pain, muscle pain or flushing

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

approved class D extinguishers. Do not use water or foam.

Extinguishing media which must not be used for safety reasons

Water.

5.2. Special hazards arising from the substance or mixture

Pyrophoric: Spontaneously flammable in air.

Hazardous Combustion Products

Nickel oxides, Fumes of aluminum or aluminum oxide, Iron oxides.

5.3. Advice for firefighters

Revision Date 20-Feb-2024

Sponge Nickel, A-4000, promoted with 2% Iron and 2.5% Chromium

Revision Date 20-Feb-2024

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Do not dry up the product.

6.2. Environmental precautions

Collect spillage. Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Sweep up and shovel into suitable containers for disposal. Keep in suitable, closed containers for disposal.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Avoid dust formation.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Store under an inert atmosphere. Protect from sunlight and store in well-ventilated place. Keep wetted with water. Keep away from open flames, hot surfaces and sources of ignition.

Technical Rules for Hazardous Substances (TRGS) 510 Class 4.2 Storage Class (LGK) (Germany)

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC

01	The Hadred Manders	European Union	Land Land II
Component	The United Kingdom	European Union	i ireiand

Revision Date 20-Feb-2024

Sponge Nickel, A-4000, promoted with 2% Iron and 2.5% Chromium

Nickel	STEL: 1.5 mg/m³ 15 min TWA: 0.5 mg/m³ 8 hr Skin		TWA: 0.5 mg/m³ 8 hr. STEL: 1.5 mg/m³ 15 min
Aluminium	STEL: 30 mg/m³ 15 min STEL: 12 mg/m³ 15 min TWA: 10 mg/m³ 8 hr TWA: 4 mg/m³ 8 hr		TWA: 1 mg/m³ 8 hr. respirable fraction STEL: 3 mg/m³ 15 min
Chromium	STEL: 1.5 mg/m ³ 15 min TWA: 0.5 mg/m ³ 8 hr	TWA: 2 mg/m³ (8hr)	TWA: 2 mg/m ³ 8 hr. STEL: 6 mg/m ³ 15 min
Molybdenum	STEL: 20 mg/m ³ 15 min TWA: 10 mg/m ³ 8 hr		

Biological limit values

List source(s):

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Nickel 7440-02-0 (86)			DNEL = 0.035mg/cm2	

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Nickel 7440-02-0 (86)	DNEL = 11.9mg/m ³		DNEL = 0.05mg/m ³	DNEL = 0.05mg/m ³
Chromium 7440-47-3 (2.5)			DNEL = 0.5mg/m ³	
Iron 7439-89-6 (2)			DNEL = 3mg/m ³	
Molybdenum 7439-98-7 (1)				DNEL = 11.7mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water	Water Intermittent	Microorganisms in	Soil (Agriculture)
		sediment		sewage treatment	
Nickel	PNEC = $7.1\mu g/L$	PNEC = 109mg/kg		PNEC = 0.33mg/L	PNEC = 29.9 mg/kg
7440-02-0 (86)		sediment dw			soil dw
Aluminium				PNEC = 20mg/L	
7429-90-5 (8.5)				_	
Chromium	PNEC = 6.5µg/L	PNEC =			PNEC = 21.1mg/kg
7440-47-3 (2.5)		205.7mg/kg			soil dw
		sediment dw			
Molybdenum	PNEC = 12.7mg/L	PNEC =		PNEC = 21.7mg/L	PNEC = 9.9mg/kg
7439-98-7 (1)		22600mg/kg		_	soil dw
1		sediment dw			

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
Nickel	PNEC = 8.6µg/L	PNEC = 109mg/kg		PNEC = 0.12mg/kg	
7440-02-0 (86)		sediment dw		food	
Molybdenum	PNEC = 2.28mg/L	PNEC = 2368mg/kg			
7439-98-7 (1)		sediment dw			

8.2. Exposure controls

Engineering Measures

Sponge Nickel, A-4000, promoted with 2% Iron and 2.5% Chromium

Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Wear safety glasses with side shields (or goggles) (European standard - EN 166)

Hand Protection Protective gloves

Glove material Natural rubber Nitrile rubber Neoprene	Breakthrough time See manufacturers recommendations	Glove thickness	EU standard EN 374	Glove comments (minimum requirement)
PVC				

Skin and body protection Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

Revision Date 20-Feb-2024

and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced **Recommended Filter type:** Particulates filter conforming to EN 143

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Particle filtering: EN149:2001 When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls Prevent product from entering drains. Do not allow material to contaminate ground water

system. Local authorities should be advised if significant spillages cannot be contained.

Solid

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State Solid Suspension

Appearance

Odor Odorless

Odor Threshold
Melting Point/Range
Softening Point
Boiling Point/Range
No data available
No data available
No information available

Flammability (liquid) Not applicable

Flammability (solid,gas) No information available

Explosion Limits No data available

Flash Point No information available Method - No information available

Autoignition TemperatureNo data availableDecomposition TemperatureNo data available

pH No information available

Viscosity Not applicable Solid

Water Solubility Insoluble in water

Revision Date 20-Feb-2024

Sponge Nickel, A-4000, promoted with 2% Iron and 2.5% Chromium

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

No data available **Vapor Pressure Density / Specific Gravity** No data available No data available **Bulk Density Vapor Density** Not applicable

Particle characteristics No data available

9.2. Other information

Evaporation Rate Not applicable - Solid

SECTION 10: STABILITY AND REACTIVITY

Solid

10.1. Reactivity Yes Spontaneously flammable in air

10.2. Chemical stability

Air sensitive.

10.3. Possibility of hazardous reactions

Hazardous Polymerization No information available.

Hazardous Reactions Pyrophoric: Spontaneously flammable in air.

10.4. Conditions to avoid

Incompatible products. Excess heat.

10.5. Incompatible materials

Acids. Oxidizing agent.

10.6. Hazardous decomposition products

Nickel oxides. Fumes of aluminum or aluminum oxide. Iron oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral No data available **Dermal** No data available Inhalation No data available

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Nickel	LD50 > 9000 mg/kg (Rat)	-	LC50 > 10.2 mg/L (Rat) 1 h
Aluminium	-	-	LC50 > 0.888 mg/L (Rat) 4 h
Iron	7500 mg/kg (Rat)	-	-
Molybdenum	-	LD50 > 2000 mg/kg (Rat)	LC50 > 5.84 mg/L (Rat) 4 h

(b) skin corrosion/irritation; No data available

(c) serious eye damage/irritation; No data available Sponge Nickel, A-4000, promoted with 2% Iron and 2.5% Chromium

(d) respiratory or skin sensitization;

Respiratory No data available No data available Skin

May cause sensitization by skin contact

No data available (e) germ cell mutagenicity;

(f) carcinogenicity; No data available

The table below indicates whether each agency has listed any ingredient as a carcinogen

Revision Date 20-Feb-2024

Component EU		UK	Germany	IARC	
Nickel			Cat. 1	Group 2B	

No data available (g) reproductive toxicity;

No data available (h) STOT-single exposure;

No data available (i) STOT-repeated exposure;

Route of exposure Inhalation **Target Organs** Lungs.

(j) aspiration hazard; Not applicable

Solid

delayed

Symptoms / effects,both acute and Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any

known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects May cause long-term adverse effects in the environment. Do not allow material to

contaminate ground water system.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Nickel	LC50: > 100 mg/L, 96h (Brachydanio rerio) LC50: = 1.3 mg/L, 96h semi-static (Cyprinus carpio)	EC50: = 1 mg/L, 48h Static (Daphnia magna) EC50: > 100 mg/L, 48h (Daphnia magna)	EC50: 0.174 - 0.311 mg/L, 96h static (Pseudokirchneriella subcapitata) EC50: = 0.18 mg/L, 72h
	LC50: = 10.4 mg/L, 96h static (Cyprinus carpio)		(Pseudokirchneriella subcapitata)

12.2. Persistence and degradability Product contains heavy metals. Discharge into the environment must be avoided. Special

pre-treatment is necessary

Insoluble in water, May persist. **Persistence** Degradability Not relevant for inorganic substances.

Degradation in sewage Contains substances known to be hazardous to the environment or not degradable in waste

treatment plant water treatment plants.

Sponge Nickel, A-4000, promoted with 2% Iron and 2.5% Chromium

12.3. Bioaccumulative potential May have some potential to bioaccumulate; Product has a high potential to bioconcentrate

 Component
 log Pow
 Bioconcentration factor (BCF)

 Chromium
 1.03 - 1.22

12.4. Mobility in soil Spillage unlikely to penetrate soil Is not likely mobile in the environment due its low water

solubility.

12.5. Results of PBT and vPvB

assessment

No data available for assessment.

12.6. Endocrine disrupting

properties

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused

Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Revision Date 20-Feb-2024

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but

application specific.

Other Information Do not flush to sewer. Waste codes should be assigned by the user based on the

application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not let this chemical enter the environment. Do not

empty into drains.

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

<u>14.1. UN number</u> UN1378

14.2. UN proper shipping name METAL CATALYST, WETTED

14.3. Transport hazard class(es) 4.2 14.4. Packing group II

ADR

14.1. UN number UN1378

14.2. UN proper shipping name METAL CATALYST, WETTED

14.3. Transport hazard class(es) 4.2 14.4. Packing group II

Sponge Nickel, A-4000, promoted with 2% Iron and 2.5% Chromium

oponge moner, A 4000, promoted with 270 horr and 2.070 omornium

IATA

14.1. UN number UN1378

14.2. UN proper shipping name METAL CATALYST, WETTED

14.3. Transport hazard class(es) 4.2 14.4. Packing group II

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk Not applicable, packaged goods

according to IMO instruments

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Nickel	7440-02-0	231-111-4	-	-	Х	X	KE-25818	X	-
Aluminium	7429-90-5	231-072-3	-	-	Х	Х	KE-00881	Х	-
Chromium	7440-47-3	231-157-5	-	-	Х	X	KE-05970	X	-
Iron	7439-89-6	231-096-4	-	-	Х	X	KE-21059	X	-
Molybdenum	7439-98-7	231-107-2	-	-	X	Х	KE-25427	X	-

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Nickel	7440-02-0	X	ACTIVE	X	-	Х	X	Х
Aluminium	7429-90-5	Х	ACTIVE	Х	-	Х	Х	Х
Chromium	7440-47-3	X	ACTIVE	X	-	Х	Х	X
Iron	7439-89-6	X	ACTIVE	X	-	Х	Х	Х
Molybdenum	7439-98-7	X	ACTIVE	X	-	Х	Х	Х

Legend: X - Listed '-' - Not Listed KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Nickel	7440-02-0	-	Use restricted. See item 27. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-
Aluminium	7429-90-5	-	Use restricted. See item 75. (see link for restriction details)	٠
Chromium	7440-47-3	-	Use restricted. See item 75. (see link for restriction details)	-
Iron	7439-89-6	-	-	-
Molybdenum	7439-98-7	-	-	-

Revision Date 20-Feb-2024

Sponge Nickel, A-4000, promoted with 2% Iron and 2.5% Chromium

Revision Date 20-Feb-2024

REACH links

https://echa.europa.eu/substances-restricted-under-reach

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Nickel	7440-02-0	Not applicable	Not applicable
Aluminium	7429-90-5	Not applicable	Not applicable
Chromium	7440-47-3	Not applicable	Not applicable
Iron	7439-89-6	Not applicable	Not applicable
Molybdenum	7439-98-7	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

See table for values

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Nickel	WGK2	Class II: 0.5 mg/m³ (Massenkonzentration)
		Krebserzeugende Stoffe - Class II : 0.5 mg/m³
		(Massenkonzentration)
Aluminium	nwg	
Chromium	nwg	Class III: 1 mg/m³ (Massenkonzentration)
Iron	nwg	
Molybdenum	nwg	

Component	France - INRS (Tables of occupational diseases)
Aluminium	Tableaux des maladies professionnelles (TMP) - RG 32
	Tableaux des maladies professionnelles (TMP) - RG 16,RG 16bis
Chromium	Tableaux des maladies professionnelles (TMP) - RG 10
Iron	Tableaux des maladies professionnelles (TMP) - RG 44,RG 44bis,RG 94

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Nickel	Prohibited and Restricted		
7440-02-0 (86)	Substances		
Chromium	Prohibited and Restricted		
7440-47-3 (2.5)	Substances		

15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has not been conducted

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H250 - Catches fire spontaneously if exposed to air

H251 - Self-heating; may catch fire

H317 - May cause an allergic skin reaction

H351 - Suspected of causing cancer

H372 - Causes damage to organs through prolonged or repeated exposure

H412 - Harmful to aquatic life with long lasting effects

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50% NOEC - No Observed Effect Concentration PBT - Persistent, Bioaccumulative, Toxic

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Health, Safety and Environmental Department Prepared By

Creation Date 17-May-2018 **Revision Date** 20-Feb-2024

Revision Summary New emergency telephone response service provider.

This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

Substances List

ENCS - Japanese Existing and New Chemical Substances AICS - Australian Inventory of Chemical Substances NZIoC - New Zealand Inventory of Chemicals

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50% POW - Partition coefficient Octanol:Water vPvB - very Persistent, very Bioaccumulative

ICAO/IATA - International Civil Aviation Organization/International Air **Transport Association**

MARPOL - International Convention for the Prevention of Pollution from

Ships

ATE - Acute Toxicity Estimate VOC - (Volatile Organic Compound)

Sponge Nickel, A-4000, promoted with 2% Iron and 2.5% Chromium

Revision Date 20-Feb-2024

materials or in any process, unless specified in the text

End of Safety Data Sheet